

- Notes:
1. Please refer to all relevant method statements for preparation and application information.
  2. All Hydroswell BentoStrip must overlap 100mm, side by side where ever there are intersections.
  3. Slurry to be applied a minimum of 70 mm either side of the Hydroswell BentoStrip.
  4. All construction joints must have Hydroswell BentoSteel installed over the top of Hydroswell BentoStrip.
  5. Drawing to read in conjunction with GH715813SV-020, Detail3.


- Legend:
- ① Xypex Concentrate Slurry
  - ② Hydroswell BentoStrip
  - ③ BentoGuard Membrane
  - ④ BentoGuard Putty 38mmx 38mm
  - ⑤ Hydroswell BF 36/52
  - ⑥ Hydroswell MF 66/32
  - ⑦ Hydroswell BentoSteel
  - Concrete containing Xypex Admix

All dimensions are in millimetres, unless stated

All dimensions to be checked on site prior to commencement of any work

Copyright protected - no part of this drawing may be reproduced without prior consent of SMR Projects Ltd

P - Preliminary Issue				R - Record Issue	
Rev	Description	Drawn by	Date	Checked	Date
-	-	-	-	-	-
-	-	-	-	-	-
-	-	-	-	-	-
-	-	-	-	-	-
-	-	-	-	-	-
-	-	-	-	-	-



MEMBRANE + ANCILLARY PRODUCTS

SMR Projects Ltd - Waterproofing Specialists

SMR House  
Beaumont Close  
Banbury  
Oxfordshire  
OX16 1TG

w: [www.smrxypex.co.uk](http://www.smrxypex.co.uk)  
e: [info@smrxypex.co.uk](mailto:info@smrxypex.co.uk)  
t: 01295 279747

Project Name:

**Typicl Xypex - BentoGuard Detail**

Title:

**Sheet pile / slab interface**

Job Number:	Date: 14/08/24		
Drawing Number: <b>XH101-ASP</b>	Rev:		
Drawn: NG	Checked: PE	Scale: NTS	ISO A3 420 x 297mm