



(Post Applied BentoGuard Membrane & BentoGuard Putty)

Notes:

1. Please refer to all relevant method statements for preparation and application information.
2. To allow this detail be included as part of warranty, the backer, Stopaq and Patch'n Plug must be installed by SMR Projects Ltd.
3. Minimum concrete thickness 200mm. For concrete less than 200mm please contact your Technical Representative.

Legend:

- ① BentoGuard Membrane
- ② BentoGuard Putty 38mmx 38mm
- ③ Stopaq
- ④ Xypex Patch n' Plug
- Concrete containing Xypex Admix

04	Drawing template updated	NG	09/02/24	DW	07/03/24
03	Revision to Products used	NG	02/05/23	AL/DW	03/05/23
02	Note 2 revised	NG	04/10/22	AL	04/10/22
01	Changes to title block	NG	23/09/22	AL	27/09/22
Rev	Description	Drawn by	Date	Checked	Date

All dimensions are in millimetres, unless stated. All dimensions to be checked on site prior to commencement of any work. Copyright protected - no part of this drawing may be reproduced without prior consent of SMR Projects Ltd.



www.smrxyper.co.uk
e.info@smrxyper.co.uk
t.01295 279747

waterproofing specialists | Hydroswell XYPEX

SMR House, Beaumont Close, Banbury, Oxfordshire, OX161TG

Project Name:
Typical Xypex - BentoGuard Detail

Drawing Title:
Typical Xypex - BentoGuard Penetration Cored

Project Number: - Date: 11/03/22

Drawing Number: XH105 Rev: 04

Drawn: NG	Checked: AL	Approved: AL	Scale: NTS	ISO A4 297 x 210mm
-----------	-------------	--------------	------------	-----------------------