



- Notes:**
1. Please refer to all relevant method statements for preparation and application information.
 2. Install BentoGuard Membrane with dark grey (Woven) Geotextile facing installer.
 3. 38 x 38mm BentoGuard Grain or Putty fillet is required if the BentoGuard Membrane is applied following the profile of the piles. If the infill between the piles is filled to give a flat surface for the BentoGuard Membrane application then the BentoGuard Grain or Putty fillet is not required.
 4. All construction joints must have Hydroswell BentoSteel installed over the top of Hydroswell BentoStrip.

- Legend:**
- ① Xypex Concentrate Slurry
 - ② Hydroswell BentoStrip
 - ③ BentoGuard Membrane
 - ④ BentoGuard Grain or Putty 38mmx 38mm
 - ⑤ Hydroswell BF 36/52
 - ⑥ Hydroswell MF 66/32
 - ⑦ Hydroswell BentoSteel
 - Concrete containing Xypex Admix

03	Drawing template updated	NG	09/02/24	DW	07/03/24
02	BentoSteel note added	NG	04/10/22	AL	04/10/22
01	Changes to legend, notes and title block	NG	23/09/22	AL	27/09/22
Rev	Description	Drawn by	Date	Checked	Date

All dimensions are in millimetres, unless stated. All dimensions to be checked on site prior to commencement of any work. Copyright protected - no part of this drawing may be reproduced without prior consent of SMR Projects Ltd.


SMR PROJECTS
 waterproofing specialists

w. www.smrrypex.co.uk
 e. info@smrypex.co.uk
 t. 01295 279747


Hydroswell XYPLEX
 SMR House, Beaumont Close, Banbury, Oxfordshire, OX161TG

Project Name: Typical Xypex - BentoGuard Detail

Drawing Title: Slab to Wall Xypex - BentoGuard Transition - Piled Wall

Project Number:	-	Date:	11/03/22
Drawing Number:	XH110	Rev:	03
Drawn:	NG	Checked:	AL
Approved:	AL	Scale:	NTS
		ISO A3	420 x 297mm

See Note 2