



Notes:

1. Please refer to all relevant method statements for preparation and application information.
2. All Hydroswell BentoStrip must overlap 100mm, side by side where ever there are intersections.
3. Slurry to be applied a minimum of 70 mm either side of the Hydroswell BentoStrip.
4. Hydroswell BF 36/52 omitted for clarity
5. All construction joints must have Hydroswell BentoSteel installed over the top of Hydroswell BentoStrip.

Legend:

- ① Xypex Concentrate Slurry
- ② Hydroswell BentoStrip
- ③ Hydroswell BF 36/52
- ④ Hydroswell BentoSteel
- Concrete containing Xypex Admix

02	Drawing template updated	NG	26/01/24	DW	07/03/24
01	BentoSteel note added	NG	03/10/22	AL	03/10/22
Rev	Description	Drawn by	Date	Checked	Date

All dimensions are in millimetres, unless stated. All dimensions to be checked on site prior to commencement of any work. Copyright protected - no part of this drawing maybe reproduced without prior consent of SMR Projects Ltd.



w. www.smrxypex.co.uk
 e. info@smrxypex.co.uk
 t. 01295 279747

Hydroswell XYPLEX

SMR House, Beaumont Close, Banbury, Oxfordshire, OX161TG

Project Name: **Xypex Standard Detail**

Drawing Title: **Day Joint in Liner Wall to Sheet Piles**

Project Number: - Date: 26/09/22

Drawing Number: **XSD033** Rev: 02

Drawn: NG	Checked: AL	Approved: AL	Scale: NTS	ISO A4 297 x 210mm
-----------	-------------	--------------	------------	------------------------------