



Notes:

- Please refer to all relevant method statements for preparation and application information.
- All Hydrowell BentoStrip must overlap 100mm, side by side where ever there are intersections.
- Slurry to be applied a minimum of 70 mm either side of the Hydrowell BentoStrip.
- Hydrowell BentoStrip water bar to be fixed to sheet pile with Hydrowell Adhesive.
- All concrete to concrete construction joints must have Hydrowell BentoSteel installed over the top of Hydrowell BentoStrip.

Legend:

- ① Xypex Concentrate Slurry
- ② Hydrowell BentoStrip
- ③ Hydrowell BF 36/52
- ④ Hydrowell BentoSteel
- ⑤ Hydrowell Adhesive
- Concrete containing Xypex Admix

02	Drawing template updated + Change to Xypex joint details	NG	26/01/24	DW	07/03/24
01	BentoSteel note added	NG	03/10/22	AL	03/10/22
Rev	Description	Drawn by	Date	Checked	Date

All dimensions are in millimetres, unless stated. All dimensions to be checked on site prior to commencement of any work. Copyright protected - no part of this drawing may be reproduced without prior consent of SMR Projects Ltd.



w. www.smrxypex.co.uk
e. info@smrxypex.co.uk
t. 01295 279747

Hydrowell XYPEx

SMR House, Beaumont Close, Banbury, Oxfordshire, OX161TG

Project Name:

Xypex Standard Detail

Drawing Title:

Slab to Sheet Pile including Day Joint

Project Number:

-

Date:

26/09/22

Drawing Number:

XSD039

Rev:

02

Drawn:

NG

Checked:

AL

Approved:

AL

Scale:

NTS

ISO A4
297 x 210mm